






DIGITAL TOUR GUIDE SYSTEM

Our noise-free tour guide system minimizes the unpleasant noise caused by interference and allows you to roam through countries across the world with the use of the programmer.

-  LCD display for battery status and channel number reading
-  Channel lock and power saving functions
-  Powered by 1 AA battery (Alkaline or NiMH) to allow 18 hours of battery life
-  Clear and noise-free sound optimize visitors' touring experience
-  Channel synchronization function



group tour



factory tour



river cruise



worship

DUR Receiver

DUT Transmitter

Chargers and Carry Bag/Case



HDC-505
5-slot charger



HDC-515
15-slot charger



HDC-525
25-slot charger



HDC-550
50-slot charger



CCW-30
30-unit carry case



TB-500
42-slot carry bag

Specifications	Tour system
Carrier frequency range	505 ~ 530 MHz (region dependent)
Power requirements	1 x AA (1.2 V 2100mAh, NiMH) or 1 x AA (1.5 V Alkaline)
Channels	17 ~ 96 (region dependent)
Charging time	8 hours
Operating range	100 m (line of sight)
Battery life (NiMH/Alkaline)	16 / 18 hours, typical
Dimensions (D x W x H)	24 x 40 x 100 (mm) (with antenna)
Weight	70 g (with battery)

* Specifications are subject to change